Ravelli il fuoco intelligente RAVELLI S.p.A. Via Kupfer, 31 25036 Palazzolo sull'Oglio (B5) Tel. + 39 030 7402939 Fax +39 030 7301758 info@ravelligroup.it - www.ravelligroup.it

## DECLARATION OF PERFORMANCE Declaration of performance according to Regulation (EU) 305/2011

## n. 089CPR13.07

1. Unique identification code of the product type:

038-00-001A, residential space heating appliance with water fired by wood pellets EN 14785:2006

- Type, batch or serial number or any other element allowing identification of the construction product as required under Art. 11(4): HRV 140 TOUCH
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Residential space heating appliance with water fired by wood pellets
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required by Art. 11 (5):
  - Ravelli S.p.A. Via A. Kupfer, 31
  - 25036 Palazzolo s/O (Bs) Italia
- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
- ---
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 3
- In case of the declaration of performance concerning a construction product covered by a harmonised standard: The notified laboratory TUV RheinlandEnergie GmbH (NB 2456) performed the determination of the product type on the basis of type testing
- under system 3 and issued test report K18792016T1
- 8. Declared performance

Harmonizedtechnicalspecification:	EN 14785:2006			
Essentialcharacteristics	Performance			
Firesafety				
Reaction to fire	AI			
Distance to combustiblematerials	Minimum distances (mm): rear = 100 sides = 150 front = 800 ceiling = floor =			
Risk of burning fuel falling out	Pass			
Emission of combustion products (at 13% of O <sub>2</sub> )	Nominal heat output CO 0,010 % NOx 140 mg/Nm <sup>3</sup> OGC 2 mg/Nm <sup>3</sup> PM 13 mg/Nm <sup>3</sup> Reduced heat output CO 0,048 % OGC 12 mg/Nm <sup>3</sup>			
Surface temperature	Pass			
Electricalsafety	Pass			
Cleanability	Pass			
Maximum operating pressure	2 bar			
Flue gas temperature at nominal heat output	156,8 °C			
Mechanical resistance(to carry a chimney/flue)	NPD			
Nominal heat output	17,2 kW			
Room heating output	2,6 kW			
Water heating output	14,6 kW			
Efficiency	Ŋ 90,0 % Nominal heat output Ŋ 91,1 % Reduced heat output			

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacture	r	_Giovanni Scarlini, CEC	(nome and title)	
Place Palazzolo s/O	Date	1-9-2016	Sign Au	-
Registro Imprese Bs 07007260966	Cod	Fiscale e P IVA 07	2007260966 Capitale Socia	ale