

RAVELLI S.p.A.

Tel. + 39 030 7402939 Fax +39 030 7301758

DECLARATION OF PERFORMANCE

Declaration of performance according to Regulation (EU) 305/2011

n. 078CPR13.07

- Unique identification code of the product type:
 - 071-00-005A, residential space heating appliance fired by wood pellets
 - EN 14785:2006
- Type, batch or serial number or any other element allowing identification of the construction product as required under Art. 11(4): OLIVIA STEEL
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Residential space heating appliance fired by wood pellets
- Name, registered trade name or registered trademark and contact address of the manufacturer as required by Art. 11 (5): Ravelli S.p.A.

Via A. Kupfer, 31

25036 Palazzolo s/O (Bs) Italia

- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: The notified laboratory TÜV RheinlandEnergie GmbH (NB 2456) performed the determination of the product type on the basis of type testing under system 3 and issued test report K17572015T1
- 8. Declared performance

Harmonizedtechnicalspecification:	EN 14785:2006			
Essentialcharacteristics	Performance			
Firesafety				
Reaction to fire	AI			
Distance to combustiblematerials	Minimum distances (mm): rear = 100 sides = 150 right, 0 left front = 800 ceiling = floor =			
Risk of burning fuel falling out	Pass			
Emission of combustion products (at 13% of O_2)	Nominal heat output CO 0,011 % NOx 158,0 mg/Nm³ OGC 5,0 mg/Nm³ PM 6,8 mg/Nm³ Reduced heat output CO 0,017 % OGC 9,26 mg/Nm³			
Surface temperature	Pass			
Electricalsafety	Pass			
Cleanability	Pass			
Maximum operating pressure				
Flue gas temperature at nominal heat output	151,6 °C			
Mechanical resistance(to carry a chimney/flue)	NPD			
Nominal heat output	8,4 kW			
Room heating output	8,4 kW			
Water heating output				
Efficiency	Π 88,9 % Nominal heat output Π 90,7 % Reduced heat output			

9.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance
	is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for a	and on behalf of the manu	facturer	Giovanni Scarlini, CE	EO	(name and title)
Place	Palazzolo s/O	Date	1-9-2016	Sign_	Hu